



Technical datasheet No.: **1038.6**

Product: POLYMAR® high gloss

Article No.: 8210 5240

| | | | |
|-----------------------------------|---|-------------------|-------------|
| Type of coating and finish | | | |
| Type of coating | PVC | | |
| Finish | both sides lacquered, high gloss | | |
| Burning behaviour | ISO 3795 <100 mm/min. | | |
| Total weight | 650 g/m ² | EN ISO 2286-2 | |
| Tensile strength warp/weft | 2500 / 2500 N/50 mm | EN ISO 1421/V1 | |
| Tear strength warp/weft | 250 / 250 N | DIN 53363 | |
| Adhesion | 20 N/cm | LB 3.04-1 | |
| Cold resistance. | -40 °C | EN 1876-1 | |
| High Temperature | +70 °C | LB 3.15 | |
| Light fastness | >6 Note, Value | EN ISO 105 B02 | |
| Crack resistance | no cracks | 100000 x @ | DIN 53359 A |
| Base fabric | | | |
| Material | PES | ISO 2076 | |
| Yarn count | 1100 dtex | ISO 2060 | |
| Weave | L 1/1 | | |

These indicated technical data are based on average results. Due to production procedures slight deviations can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.